

Product Introductions

- Max Working Pressure: 700 Bar
- Carry handles for easy portability
- Professional choice for wide range of industrial applications
- Large oil capacities to power a wide range of cylinder or tools



Specification

Model	Pressure Rating (bar)		Oil Volume per Stroke (ml)		Output Interface	Oil Capacity (ml)	Size (mm)
	A	B	A	B			
P-392	13	700	11.26	2.47	3/8NPT	901	533 x 157 x 120
P-80	25	700	16.22	2.46	3/8NPT	2200	539 x 146 x 174
P-84	25	700	16.22	2.46	3/8NPT	2200	539 x 146 x 174
P-462	14	700	126.2	4.75	3/8NPT	7423	742 x 308 x 270
P-464	14	700	126.2	4.75	3/8NPT	7423	742 x 308 x 270

Product Introductions

- Built-in safety valve ensuring operating safety against overloading
- Gauge is oil filled to prohibit shock load damage and includes an external rubber guard for added protection. For light and corrosion free purposes
- The Air Cylinder and Piston are made from 6061-T6 Aluminium Alloy
- Air exhaust muffler for quieter operation. Air and oil inlet filters for reduced risk of damage from contamination
- All air pumps are designed to be used with single acting cylinders



Specification

Model	Usable Oil (cm3)	Pressure Rating (bar)		Oil Capacity (cm3)		Dimensions (cm)			Control	Oil Tank Material	Weight (kg)
		1st Stage	2nd Stage	1st Stage	2nd Stage	L	W	H			
F001	2296	0-6	700	820	130	31.24	17.02	19.05	Foot	Plastic	11.8
F002A	1607	0-6	700	820	130	26.16	13.46	18.54	Foot	Aluminum	8.6
F002P	1607	0-6	700	820	130	26.16	13.46	18.54	Foot	Plastic	8.2
F003	4510	0-6	700	820	130	31.75	17.78	19.05	Foot	Steel	12.7
F004	7248	0-6	700	820	130	27.94	22.35	25.4	Foot	Steel	16
F005	1607	0-6	700	820	130	26.16	13.46	18.54	Hand	Aluminum	9.5